




ENERGY

MITSUBISHI ELECTRIC CORPORATION


MXZ-4F80VF3
MSZ-LN18/18/18/25VG2

SEER



kW **8.0**
SEER **7.6**
kWh/annum **368**

SCOP



kW	X	7.0	X
SCOP	X	4.1	X
kWh/annum	X	2389	X



58dB



65dB



626/2011

PRODUCT INFORMATION (*1)							
ROOM AIR CONDITIONER		INDOOR MODEL 1/2/3 INDOOR MODEL 4/5/6 OUTDOOR MODEL	MSZ-LN18VG2 / MSZ-LN18VG2 / MSZ-LN18VG2 MSZ-LN25VG2 / - / - MXZ-4F80VF3				
Function (indicate if present)		If function includes heating: Indicate the heating season the information relates to, Indicated values should relate to one heating season at a time, Include at least the heating season 'Average'.					
cooling		Y	Average (mandatory) Y				
heating		Y	Warmer (if designated) N				
			Colder (if designated) N				
Item	symbol	value	unit	Item	symbol	value	unit
Design load				Seasonal efficiency			
cooling	Pdesignc	8,0	kW	cooling	SEER	7,6	-
heating/Average	Pdesignh	7,0	kW	heating/Average	SCOP/A	4,1	-
heating/Warmer	Pdesignh	x	kW	heating/Warmer	SCOP/W	x	-
heating/Colder	Pdesignh	x	kW	heating/Colder	SCOP/C	x	-
Declared capacity for cooling, at indoor temperature 27(19)°C and outdoor temperature Tj				Declared energy efficiency ratio, at indoor temperature 27(19)°C and outdoor temperature Tj			
Tj=35°C	Pdc	8,00	kW	Tj=35°C	EERd	3,56	-
Tj=30°C	Pdc	5,95	kW	Tj=30°C	EERd	5,81	-
Tj=25°C	Pdc	3,80	kW	Tj=25°C	EERd	9,50	-
Tj=20°C	Pdc	2,50	kW	Tj=20°C	EERd	12,80	-
Declared capacity for heating/Average season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance/Average season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	6,20	kW	Tj=-7°C	COPd	2,70	-
Tj=2°C	Pdh	4,00	kW	Tj=2°C	COPd	4,07	-
Tj=7°C	Pdh	2,60	kW	Tj=7°C	COPd	5,20	-
Tj=12°C	Pdh	1,75	kW	Tj=12°C	COPd	6,30	-
Tj=bivalent temperature	Pdh	6,20	kW	Tj=bivalent temperature	COPd	2,70	-
Tj=operating limit	Pdh	4,80	kW	Tj=operating limit	COPd	2,20	-
Declared capacity for heating/Warmer season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance/Warmer season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=2°C	Pdh	x	kW	Tj=2°C	COPd	x	-
Tj=7°C	Pdh	x	kW	Tj=7°C	COPd	x	-
Tj=12°C	Pdh	x	kW	Tj=12°C	COPd	x	-
Tj=bivalent temperature	Pdh	x	kW	Tj=bivalent temperature	COPd	x	-
Tj=operating limit	Pdh	x	kW	Tj=operating limit	COPd	x	-
Declared capacity for heating/Colder season, at indoor temperature 20°C and outdoor temperature Tj				Declared coefficient of performance/Colder season, at indoor temperature 20°C and outdoor temperature Tj			
Tj=-7°C	Pdh	x	kW	Tj=-7°C	COPd	x	-
Tj=2°C	Pdh	x	kW	Tj=2°C	COPd	x	-
Tj=7°C	Pdh	x	kW	Tj=7°C	COPd	x	-
Tj=12°C	Pdh	x	kW	Tj=12°C	COPd	x	-
Tj=bivalent temperature	Pdh	x	kW	Tj=bivalent temperature	COPd	x	-
Tj=operating limit	Pdh	x	kW	Tj=operating limit	COPd	x	-
Tj=-15°C	Pdh	x	kW	Tj=-15°C	COPd	x	-
Bivalent temperature				Operating limit temperature			
heating/Average	Tbiv	-7	°C	heating/Average	Tol	-15	°C
heating/Warmer	Tbiv	x	°C	heating/Warmer	Tol	x	°C
heating/Colder	Tbiv	x	°C	heating/Colder	Tol	x	°C
Cycling interval capacity				Cycling interval efficiency			
for cooling	Pcycc	x	kW	for cooling	EERcyc	x	-
for heating	Pcyhc	x	kW	for heating	COPcyc	x	-
Degradation co-efficient	Cdc	0,25	-	Degradation co-efficient	Cdh	0,25	-
Electric power input in power modes other than 'active mode'				Annual electricity consumption			
off mode	POFF	4	W	cooling	QCE	368	kWh/a
standby mode	PSB	4	W	heating/Average	QHE	2389	kWh/a
thermostat - off mode	PTO	21	W	heating/Warmer	QHE	x	kWh/a
crankcase heater mode	PCK	0	W	heating/Colder	QHE	x	kWh/a
Capacity control (indicate one of three options)				Other items			
fixed		N		Sound power level (indoor1-4/outdoor)	LWA	58/65	dB(A)
staged		N		Global warming potential	GWP (*2)	675	kgCO2eq.
variable		Y		Rated air flow (indoor1-4/outdoor)	-	690/2418	m ³ /h
Contact details for obtaining more information	MITSUBISHI ELECTRIC CORPORATION SHIZUOKA WORKS 3-18-1, Oshika, Suruga-ku, Shizuoka 422-8528, Japan E-mail: melshierp@nb.MitsubishiElectric.co.jp						

(*1) This information is based on the "product information requirement" in COMMISSION REGULATION (EU) No206/2012,

(*2) This GWP value is based on Regulation (EU) No.517/2014 from IPCC 4th Assessment Report.

For Regulation (EU) No.626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.

TECHNICAL DOCUMENTATION (1)

ROOM AIR CONDITIONER	INDOOR MODEL 1	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 2	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 3	MSZ-LN18VG2	307H890W233D (mm)
	INDOOR MODEL 4	MSZ-LN25VG2	307H890W233D (mm)
	INDOOR MODEL 5	-	-
	INDOOR MODEL 6	-	-
	OUTDOOR MODEL	MXZ-4F80VF3	710H840W330D (mm)

Function	
cooling	Y
heating	Y


The heating season	
Average (mandatory)	Y
Warmer (if designated)	N
Colder (if designated)	N

Capacity control	
fixed	N
staged	N
variable	Y

Item	symbol	value	unit
Seasonal efficiency (2)			
cooling	SEER	7.6	-
heating/Average	SCOP/A	4.1	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Energy efficiency class			
cooling	SEER	A++	-
heating/Average	SCOP/A	A+	-
heating/Warmer	SCOP/W	x	-
heating/Colder	SCOP/C	x	-

Other items			
Sound power level (indoor1-4/outdoor)	LWA	58/65	dB(A)
Refrigerant	-	R32	-
Global warming potential	GWP (3)	675	kgCO ₂ eq.

identification and signature of the person empowered to bind the supplier	
	Tadashi Saito Department Manager, Quality Assurance Department MITSUBISHI ELECTRIC CONSUMER PRODUCTS(THAILAND) CO.,LTD

- (1) This information is based on COMMISSION DELEGATED REGULATION (EU)No626/2011,
 (2) SEER/SCOP values are measured based on FprEN 14825:2016: Testing and rating at part load conditions and calculation of seasonal performance.
 (3) This GWP value is based on Regulation (EU) No.517/2014 from IPCC 4th Assessment Report.
 For Regulation (EU) No.626/2011, which cites the IPCC Third Assessment Report, Climate Change 2001, the GWP is 550.