TECHNICAL DOCUMENTATION

TECHNICAL DOCUMENTATION & PRODUCT INFORMATION

PRODUCT MODEL JT-SB216KSN

Requirements		Information
(1)	Overall efficiency (%)	52.7
<u> </u>	Measurement category	C
(3)	Efficiency category	Static
	Efficiency grade(N)	61
(5)	VSD	A variable speed drive is integrated within the fan
(6)	Year of manufacture	2012
(7)	Manufacturer	MITSUBISHI ELECTRIC CORPORATION HEAD OFFICE: TOKYO BUILDING 2-7-3, MARUNOUCHI, CHIYODA- KU, TOKYO 100-8310, JAPAN AUTHORIZED REPRESENTATIVE IN EU: MITSUBISHI ELECTRIC EUROPE B.V. HARMAN HOUSE, 1GEORGE STREET, UXBRIDGE, MIDDLESEX UB8 1QQ, U.K. COMMERCIAL REGISTRATION NO.33279602
(8)	Model number	JT-SB216JSH,JT-SB216KSN
(9)	Motor power input (kW)	0.66
	Flow rate (m ³ /s)	0.05
	Pressure (Pa)	6680
(10)	Rotations per minute	20600
	Specific ratio	1.0
(12)	Information relevant for facilitating disassembly, recycling or disposal at end-of-life	Your product should be disposed of separately from household waste in line with local laws and regulations. When this product reaches its end of life, dispose of it at your local waste collection point/recycling centre. The separate collection and recycling of your product at the time of disposal will help conserve natural resources and ensure that it is recycled in a manner that protects human health and the environment. For more information for WEEE recyclers please contact us at http://www.mitsubishielectric.eu/contact_us_form
(13)	Information relevant to minimise impact on the environment and ensure optimal life expectancy as regards installation, use and maintenance of the fan Description of additional	Remove dust on air filter around once a week. Empty the drain water at least once a week before the drain water exceeds the full line.
(14)	items used when determining the fan energy efficiency	The optimistic fan efficiency is measured in the composition of fan, motor and fan casing only.