TECHNICAL DOCUMENTATION

TECHNICAL DOCUMENTATION & PRODUCT INFORMATION

PRODUCT MODEL PUCY-P300YKA(-BS)

Deminerate II.C. C		
	uirements	Information
(1)	Overall efficiency (%)	51.7
	Measurement category	A
(3)	Efficiency category	STATIC
(4)	Efficiency grade(N)	40
(5)	VSD	The VSD is integrated within the fan
(6)	Year of manufacture	2014
(7)	Manufacturer	MITSUBISHI ELECTRIC CORPORATION HEAD OFFICE: TOKYO BUILDING 2-7-3, MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN AUTHORIZED REPRESENTATIVE IN EU: MITSUBISHI ELECTRIC EUROPE B.V. HARMAN HOUSE, 1GEORGE STREET, UXBRIDGE, MIDDLESEX UB8 1QQ, U.K. COMMERCIAL
(8)	Model number	PUCY-P300YKA(-BS)
	Motor power input (kW)	0.56
(9)	Flow rate (m ³ /s)	3.08
	Pressure (Pa)	93.6
(10)	Rotations per minute	761
	Specific ratio	1.0
(12)	Information relevant for facilitating disassembly, recycling or disposal at end-of-life	Your product should be disposed of separately from household waste in line with local laws and regulations. When this product reaches its end of life, dispose of it at your local waste collection point/recycling centre. The separate collection and recyc
(13)	Information relevant to minimise impact on the environment and ensure optimal life expectancy as regards installation, use and maintenance of the fan Description of additional	In addition to daily checks (eg cleaning of filters), periodic maintenance and checks by a skilled technician are required to ensure that the unit is maintained in a good condition for a long period of time, and that it may be used with confidence.
(14)	items used when determining the fan energy efficiency	